

Interface Description

ServiceCommon_REST



Revision date: 25.08.2021

TecAlliance GmbH

Contents

Module Details

1. CommonController

ObjectModel

1. ApplicationText
2. ApplicationTextMsg
3. ApplicationTextsMsg
4. CountriesMsg
5. Country
6. GetAdOnlyForReferenceTextMsg
7. GetInNotToOrderTextMsg
8. GetWorkPosCompositeTimeTextMsg
9. GetWorkPosTecRmiTimeTextMsg
10. KindOfLinkTypes
11. KindOfModule
12. Language
13. Language
14. LanguagesMsg
15. LinkTypeData
16. QualifierCollection
17. QualifierCollectionsMsg
18. QualifierData
19. QualifierGroup
20. QualifierGroupListMsg
21. VersionInfo
22. WorkPosOnlyForReferenceTextMsg

Module Details

1. CommonController

1.1. Summary

Area [RestRMI.Areas.Common.Controllers.CommonController](#) provides common web service methods. With these methods application texts, the country and language list, etc. can be fetched.

1.2. Detailed Module Documentation

1.2.1. Properties

- **HttpContext ActionContext**
No description available
- **HttpConfiguration Configuration**
No description available
- **HttpContext ControllerContext**
No description available
- **string Ip**
Gets the IP.
- **ModelStateDictionary ModelState**
No description available
- **HttpRequestMessage Request**
No description available
- **HttpContext RequestContext**
No description available
- **UrlHelper Url**
No description available
- **IPrincipal User**
No description available

1.2.2. Methods

- **IEnumerable<[ApplicationText](#)> ApplicationTexts([ApplicationTextsMsg](#) input)**
Delivers a collection of all application text ids and the corresponding texts in the selected language.

Parameter

input - Instance of the message class `ApplicationTextsMsg`.

Returns

A collection of application texts.

- string ApplicationText(ApplicationTextMsg input)

Delivers the application text with the given id in the selected language.

Parameter

input - Instance of the message class ApplicationTextMsg.

Returns

An application text.

- void Ping()

A ping for the API to test if the service is available and running.

- IEnumerable<Country> Countries(CountriesMsg input)

Retrieves a collection of all countries supported by the system. Countries codes are referring to the ISO 3166-1 standard.

Remarks

Calling country specific functions with a country parameter not supported by the system will result in an exception.

Parameter

input - Instance of the message class CountriesMsg.

Returns

A collection of supported countries.

- IEnumerable<Language> Languages(LanguagesMsg input)

Retrieves a collection of all languages supported by the system. Language codes are referring to the ISO 639-1 standard. By passing null as LanguagesMsg.LanguageCode the result will be a collection where each language name is written in his own language (eg: en -> English (GB); de - > Deutsch; ru -> ; etc). Passing a valid language code by this property all the language names will be in the given language.

Remarks

Calling language specific functions with a language parameter not supported by the system will result in an exception.

Parameter

input - Instance of the message class LanguagesMsg.

Returns

A collection of supported languages.

- IEnumerable<QualifierGroup> QualifierGroupList(QualifierGroupListMsg input)

Delivers a collection of qualifier groups in the given language.

Parameter

input - Instance of the message class QualifierGroupListMsg.

Returns

A collection of qualifier group.

- IEnumerable<LinkTypeData> GetPossibleLinkTypes()

Delivers a collection of possible values for the enum KindOfLinkTypes.

Returns

A collection of link types.

- string WorkPosOnlyForReferenceText(WorkPosOnlyForReferenceTextMsg input)

Gets the text for explaining the 'only for reference' flag in the labour times, maintenance data or basket module.

Parameter

input - Instance of the message class WorkPosOnlyForReferenceTextMsg.

Returns

A text which contains an explanation what the flag 'only for reference' means.

- string GetAdOnlyForReferenceText(GetAdOnlyForReferenceTextMsg input)

Gets the text explaining the 'only for reference flag' in technical data or filling amounts in the basket module.

Parameter

input - Instance of the message class GetAdOnlyForReferenceTextMsg.

Returns

A text which contains an explanation what the flag 'only for reference' means.

- string GetInNotToOrderText(GetInNotToOrderTextMsg input)

Gets the text explaining the 'not to order' flag in the spare part proposal.

Parameter

input - Instance of the message class GetInNotToOrderTextMsg.

Returns

A text which contains an explanation what the flag 'not to order' means.

- string GetWorkPosTecRmiTimeText(GetWorkPosTecRmiTimeTextMsg input)

Get the text for explaining the 'TecRMI work time' flag in the labour times, maintenance data or basket module.

Parameter

input - Instance of the message class GetWorkPosTecRmiTimeTextMsg.

Returns

A string which contains an explanation what the flag 'TecRMI work time' means.

- string GetWorkPosCompositeTimeText(GetWorkPosCompositeTimeTextMsg input)

Gets the text explaining the 'composite time' flag in the labour times, maintenance data or basket module.

Parameter

input - Instance of the message class GetWorkPosCompositeTimeTextMsg.

Returns

A string which contains an explanation what the flag 'composite time' means.

- VersionInfo VersionInfo()

Gets the build number of the release, the version number of the solution and the DB Version number.

Returns

An object with the build number of the release, the version number of the solution and the DB Version number

- IEnumerable<QualifierCollection> QualifierCollections(QualifierCollectionsMsg input)

Delivers a collection of detailed information about the given qualifier collection ids.

Parameter

input - Instance of the message class QualifierCollectionsMsg.

Returns

A collection of qualifier collection.

Object Model

1. ApplicationText

1.1. Summary

Class **ApplicationText** represents an text which is used in the application.

1.2. Detailed Module Documentation

1.2.1. Properties

- **int ApplicationTextId**

Gets or sets the id of the application text.

Property-Value

The application text id.

- **string Text**

Gets or sets the application text.

Property-Value

The text.

2. ApplicationTextMsg

2.1. Summary

Class [RestRMI.Areas.Common.Models.ApplicationTextMsg](#) contains the properties which are necessary to call the web service method `ApplicationText(ApplicationTextMsg)`.

2.2. Detailed Module Documentation

2.2.1. Properties

- **string LanguageCode**

Gets or sets the 2-letter international language code as defined by ISO 639-1.

Property-Value

The ISO language code.

- **int TextId**

Gets or sets the identifier of the text.

Property-Value

The identifier of the text.

3. ApplicationTextsMsg

3.1. Summary

Class [RestRMI.Areas.Common.Models.ApplicationTextsMsg](#) contains the properties which are necessary to call the web service method `ApplicationTexts(ApplicationTextsMsg)`.

3.2. Detailed Module Documentation

3.2.1. Properties

- **string LanguageCode**

Gets or sets the 2-letter international language code as defined by ISO 639-1.

Property-Value

The ISO language code.

4. CountriesMsg

4.1. Summary

Class [RestRMI.Areas.Common.Models.CountriesMsg](#) contains the properties which are necessary to call the web service method `Countries(CountriesMsg)`.

4.2. Detailed Module Documentation

4.2.1. Properties

- **KindOfModule** KindOfModule

Gets or sets the kind of module after which the collection of supporting countries should be filtered.

Property-Value

The module.

- **string LanguageCode**

Gets or sets the 2-letter international language code as defined by ISO 639-1.

Property-Value

The ISO language code.

5. Country

5.1. Summary

Class **Country** represents a country in the AuDaLib. It contains all important informations like **Name**, **ISO CountryCode**, **Currency**, etc.

5.2. Detailed Module Documentation

5.2.1. Properties

- **string CountryCode**

Gets or sets the 2-letter international country code as defined by ISO 3166-1.

Property-Value

The country code.

- **int CountryId**

Gets or sets the id of the country.

Property-Value

The country id.

- **string CountryName**

Gets or sets the name of the country.

Property-Value

The name of the country.

- **string Currency**

Gets or sets the currency of the country.

Property-Value

The currency.

- **Nullable<Decimal> ExchangeRate**

Gets or sets the exchange rate at which Euro is the reference currency.

Property-Value

The exchange rate.

5.2.2. Methods

- **string ToString()**

Returns a string that represents the current object.

Returns

A string that represents the current object.

6. GetAdOnlyForReferenceTextMsg

6.1. Summary

Class [RestRMI.Areas.Common.Models.GetAdOnlyForReferenceTextMsg](#) contains the properties which are necessary to call the web service method `GetInNotToOrderText(GetInNotToOrderTextMsg)`.

6.2. Detailed Module Documentation

6.2.1. Properties

- **string LanguageCode**

Gets or sets the 2-letter international language code as defined by ISO 639-1.

Property-Value

The ISO language code.

7. GetInNotToOrderTextMsg

7.1. Summary

Class [RestRMI.Areas.Common.Models.GetInNotToOrderTextMsg](#) contains the properties which are necessary to call the web service method `GetInNotToOrderText(GetInNotToOrderTextMsg)`.

7.2. Detailed Module Documentation

7.2.1. Properties

- **string LanguageCode**

Gets or sets the 2-letter international language code as defined by ISO 639-1.

Property-Value

The ISO language code.

8. GetWorkPosCompositeTimeTextMsg

8.1. Summary

Class [RestRMI.Areas.Common.Models.GetWorkPosCompositeTimeTextMsg](#) contains the properties which are necessary to call the web service method `GetWorkPosCompositeTimeText(GetWorkPosCompositeTimeTextMsg)`.

8.2. Detailed Module Documentation

8.2.1. Properties

- **string LanguageCode**

Gets or sets the 2-letter international language code as defined by ISO 639-1.

Property-Value

The ISO language code.

9. GetWorkPosTecRmiTimeTextMsg

9.1. Summary

Class [RestRMI.Areas.Common.Models.GetWorkPosTecRmiTimeTextMsg](#) contains the properties which are necessary to call the web service method `GetWorkPosTecRmiTimeText(GetWorkPosTecRmiTimeTextMsg)`.

9.2. Detailed Module Documentation

9.2.1. Properties

- **string LanguageCode**

Gets or sets the 2-letter international language code as defined by ISO 639-1.

Property-Value

The ISO language code.

10. KindOfLinkTypes

10.1. Summary

Enum **KindOfLinkTypes** specifies the kinds of link types.

10.2. Remarks

The AuDaLib includes several methods that return HTML documents as strings. Some of the HTML documents may contain links. The **href** attribute of the links follows a certain scheme: e.g. href="someUrl/pa1205p", where "someUrl/" is the link URL, "p" is the link separator, "a" is the kind of link type represented as char and "1205" is the link id. The kind of link type determines how the link id has to be interpreted and, therefore, determines the target module the link is referencing. The enumerators can be casted into chars. Altogether, a link can be evaluated on the web server before the HTML is sent to the client, or handled in an embedded browser control using the relevant navigation events.

10.3. Detailed Module Documentation

10.3.1. Enums

- **None**

No link.

- **AdItemMpld**

A link to an item mount position from the adjustment data module.

- **FusesBoxItemMpld**

Unused at the moment.

- **BgItemGroup**

A link to an item group from the body graphics module.

- **DiagnosisItemId**

A link to an item from the diagnosis module.

- **ErrorcodeManualId**

A link to an error code manual.

- **Fuses**

A link to fuses.

- **HotSpotGenArt**

A link to a generic article.

- **BgMainGroupId**

A link to a main group from the body graphics module.

- **TmItemMpid**

A link to an item mount position from the technical manuals module.

- **DiagnosticContentId**

Unused at the moment.

- **Unused_K**

Unused at the moment.

- **LockedItem**

A link to an item for which access is denied because the user has no permissions to access the referenced item.

- **TmManualId**

A link to a manual from the technical manuals module.

- **OeSparePartNo**

A link to a OE spare part no from a technical manual.

- **WdMainGroupId**

A link to main group from the wiring diagrams module.

- **Image**

A link to an image.

- **Unused_Q**

Unused at the moment.

- **Unused_R**

Unused at the moment.

- **BgSubGroupId**

A link to a sub group from the body graphics module.

- **VehicleTreeTypeId**

A link to a vehicle type from the vehicle tree module.

- **Unused_U**

Unused at the moment.

- **Unused_V**

Unused at the moment.

- **WdItemMpid**

A link to an item mount position from the wiring diagrams module.

- **Unused_X**

Unused at the moment.

- **ImageLinkId**

A link from an image, currently used for partposition module.

- **Unused_Z**

Unused at the moment.

11. KindOfModule

11.1. Summary

Enum **KindOfModule** specifies the kind of modules. This enum is used in order to get the correct set of countries in the appropriate method.

11.2. Detailed Module Documentation

11.2.1. Enums

- **Default**

The default module.

- **Coo**

The costs of ownership module.

- **CooNew**

The costs of ownership new module.

- **AD**

The technical data module

- **BG**

The graphical selection module

- **LT**

The labour times module.

- **MD**

The maintenance data module.

- **DI**

The diagnostics data module.

- **SOS**

The SOS data module.

- **TD**

The tyre data module.

- **TM**

The technical manuals module.

- **WD**

The wiring diagram module.

- **CO**

The component tree module.

- **CooUser**

The costs of ownership user section module.

- **Ctrl**

The Control module.

- **IN**

The invoice data module.

- **VT**

The vehicle tree module.

- **Info**

The information data module.

- **Portal**

The Portal module.

- **FR**

The fuse and relays module.

- **MP**

The mount position module.

- **CWD**

The comfort wiring diagram module.

- **Paint**

The paint module.

12. Language

12.1. Summary

Language

12.2. Detailed Module Documentation

12.2.1. Properties

- **string Code**

Gets the code.

Property-Value

The code.

- **CultureInfo Culture**

Gets the culture.

Property-Value

The culture.

- **int Id**

Gets the id.

Property-Value

The id.

- string IetfTag

Gets the ietf tag.

Property-Value

The ietf tag.

- string Name

Gets the name.

Property-Value

The name.

12.2.2. Methods

- bool Equals(Object obj)

Determines whether the specified System.Object is equal to this instance.

Parameter

obj - The System.Object to compare with this instance.

Returns

true if the specified System.Object is equal to this instance; otherwise, false.

- int GetHashCode()

Returns a hash code for this instance.

Returns

A hash code for this instance, suitable for use in hashing algorithms and data structures like a hash table.

- string ToString()

Returns a System.String that represents this instance.

Returns

A System.String that represents this instance.

- bool Equals(Language other)

Indicates whether the current object is equal to another object of the same type.

Parameter

other - An object to compare with this object.

Returns

true if the current object is equal to the parameter; otherwise, false.

- `int AuDaLib.Base.Composite.Shared.Data.References.ILanguageReference.get_Languageld()`

13. Language

13.1. Summary

Class **Language** represents a language in the AuDaLib and contains the important informations like the **id**, **name**, etc.

13.2. Detailed Module Documentation

13.2.1. Properties

- **int IsCompleteFilled**

Gets or sets a value determining whether all texts are available in this language.

Property-Value

The value determining whether the language is complete filled or not.

- **string LanguageCode**

Gets or sets the 2-letter international language code as defined by ISO 639-1.

Property-Value

The language code.

- **int Languageld**

Gets or sets the id of the language.

Property-Value

The language id.

- **string LanguageName**

Gets or sets the name of the language.

Property-Value

The name of the language.

14. LanguagesMsg

14.1. Summary

Class [RestRMI.Areas.Common.Models.LanguagesMsg](#) contains the properties which are necessary to call the web service method `Languages(LanguagesMsg)`.

14.2. Detailed Module Documentation

14.2.1. Properties

- **string LanguageCode**

Gets or sets the 2-letter international language code as defined by ISO 639-1.

By passing null the result of the web service method Languages

will be a collection where each language name is in his own language (eg: en -> English (GB); de -> Deutsch; ru -> ; etc.

Passing a valid language code by this property all the language names will be in the given language.

Property-Value

The ISO language code.

15. LinkTypeData

15.1. Summary

Class [RestRMI.Areas.Common.Models.Messages.LinkTypeData](#) contains the information which character is assigned to an enumeration value of KindOfLinkTypes.

15.2. Detailed Module Documentation

15.2.1. Properties

- **KindOfLinkTypes** KindOfLink

Gets or sets the kind of link.

Property-Value

The kind of link.

- **char LinkCharacter**

Gets or sets the link character.

Property-Value

The link character.

16. QualifierCollection

16.1. Summary

Class **QualifierCollection** represents a qualifier collection having a list of separate qualifiers from which the collection is build up. The qualifier collection delivers a further differentiation for an item.

16.2. Detailed Module Documentation

16.2.1. Properties

- **int QualCollId**

Gets or sets the id of the qualifier collection.

Property-Value

The qualifier collection id.

- **string QualColText**

Gets or sets the text of the qualifier collection.

Property-Value

The qualifier collection text.

- **List<QualifierData> Qualifiers**

Gets or sets the collection qualifiers where this qualifier collection is build up.

Property-Value

The individual qualifiers.

17. QualifierCollectionsMsg

17.1. Summary

Class [RestRMI.Areas.Common.Models.QualifierCollectionsMsg](#) contains the properties which are necessary to call the web service method `QualifierCollections(QualifierCollectionsMsg)`.

17.2. Detailed Module Documentation

17.2.1. Properties

- **string LanguageCode**

Gets or sets the 2-letter international language code as defined by ISO 639-1.

Property-Value

The ISO language code.

- **List<Int32> QualColIds**

Gets or sets a collection of qualifier collection ids.

Property-Value

The qualifier collection ids.

18. QualifierData

18.1. Summary

Class `QualifierData` represents a single qualifier. Any qualifier collection is build up from such single qualifiers.

18.2. Detailed Module Documentation

18.2.1. Properties

- **int QualifierGroupId**

Gets or sets the id of the qualifier group.

Property-Value

The qualifier group id.

- string QualifierGroupName

Gets or sets the name of the qualifier group.

Property-Value

The name of the qualifier group.

- int QualifierId

Gets or sets the id of the qualifier.

Property-Value

The qualifier id.

- string QualifierText

Gets or sets the text of the qualifier.

Property-Value

The qualifier text.

19. QualifierGroup

19.1. Summary

Class **QualifierGroup** represents a qualifier group. A qualifier group divides the plenty of qualifiers into logical groups like body, engine, air-conditioning system, etc.

19.2. Detailed Module Documentation

19.2.1. Properties

- int QualifierGroupId

Gets or sets the id of the qualifier group.

Property-Value

The qualifier group id.

- string QualifierGroupName

Gets or sets the name of the qualifier group.

Property-Value

The name of the qualifier group.

20. QualifierGroupListMsg

20.1. Summary

Class [RestRMI.Areas.Common.Models.QualifierGroupListMsg](#) contains the properties which are

necessary to call the web service method `QualifierGroupList(QualifierGroupListMsg)`.

20.2. Detailed Module Documentation

20.2.1. Properties

- **string LanguageCode**

Gets or sets the 2-letter international language code as defined by ISO 639-1.

Property-Value

The ISO language code.

21. VersionInfo

21.1. Summary

A version information data.

21.2. Detailed Module Documentation

21.2.1. Properties

- **string BuildNumber**

Gets or sets the build number.

Property-Value

The build number.

- **string DbVersionNumber**

Gets or sets the db version number.

Property-Value

The db version number.

- **string VersionNumber**

Gets or sets the version number.

Property-Value

The version number.

22. WorkPosOnlyForReferenceTextMsg

22.1. Summary

Class [RestRMI.Areas.Common.Models.WorkPosOnlyForReferenceTextMsg](#) contains the properties which are necessary to call the web service method

`WorkPostOnlyForReferenceText(WorkPostOnlyForReferenceTextMsg)`.

22.2. Detailed Module Documentation

22.2.1. Properties

- **string LanguageCode**

Gets or sets the 2-letter international language code as defined by ISO 639-1.

Property-Value

The ISO language code.